

# Hempafloor

Ultimate protection for floors

As a world-leading supplier of trusted coating solutions, Hempel is a global company with strong values, working with customers in the protective, marine, decorative, container and yacht industries. Hempel factories, R&D centres and stock points are established in every region across the globe, Hempel's coatings protect surfaces, structures and equipment. They extend asset lifetimes, reduce maintenance costs and make homes and workplaces safer and more colourful.

Hempel was founded in Copenhagen, Denmark in 1915. It is proudly owned by the Hempel Foundation, which ensures a solid economic base for the Hempel Group and supports cultural, social, humanitarian and scientific purposes around the world.

#### Hempel Qatar

Block 212, Street 16  
 Salwa Industrial Area  
 P.O.Box 3484, Doha  
 State of Qatar  
 Tel: +974 4455 9000  
 Fax: +974 4460 0901

#### Hempel Emirates

Interchange 8  
 Al Dhaid Road  
 Plot 698/G, Sajaa Area  
 P.O.Box 2000, Sharjah  
 United Arab Emirates  
 Tel: +971 6 531 0140  
 Fax: +971 6 531 0141

#### Hempel Oman

Ghala Industrial Area  
 Beside Komatsu  
 Building No 1280  
 Way No 5217  
 P.O. Box 1260, PC 112  
 Muscat, Sultanate of Oman  
 Tel: +968 24 592759  
 Fax: +968 24 596895

#### Hempel Abu Dhabi

Plot No 37, Sector M-15  
 Mussafah Industrial Area  
 P.O.Box 47006, Abu Dhabi  
 United Arab Emirates  
 Tel: +971 2 5552279  
 Fax: +971 2 5553379

#### Hempel Dammam

First Industrial Area  
 First Industrial Area  
 Fourth Road, Bn Zheer  
 Street P.O.Box 1077,  
 Dammam 31431  
 Kingdom of Saudi Arabia  
 Tel: +966 13 847 1616  
 Fax: +966 13 847 1816

#### Hempel Jeddah

Al Suhaili Commercial Centre,  
 Siteen Street,  
 Al Rabwah District,  
 P.O.Box 6783, Jeddah 21452  
 Kingdom of Saudi Arabia  
 Tel: +966 12 257 4567  
 Fax: +966 12 275 2828

#### Hempel Riyadh

Bldg. No. 6371  
 King Abdulaziz Road  
 P.O.Box 3977, Riyadh 11481  
 Kingdom of Saudi Arabia  
 Tel: +966 11 497 7839  
 Fax: +966 11 487 8012

#### Hempel Bahrain

Mina Salman Industrial Area  
 Building 314, Road  
 4306, Block 343  
 P.O.Box 997, Manama  
 Kingdom of Bahrain  
 Tel: +973 1772 8668  
 Fax: +973 1782 7327

#### Hempel Kuwait

Shuwaikh Industrial Area  
 Block B, Street No. 30,  
 Plot No. 119  
 P.O.Box 3400,  
 Safat 13034,  
 State of Kuwait  
 Tel: +965 2 202 0700  
 Fax: +965 2 484 3307


Ver 8 - 2023 / 16480

 /HempelDecorativeME

 /HempelDecoME

 /HempelPaintsArabia

 /Hempel Decorative Middle East




Think Green, Go Paperless

# Hempafloor colours

Hempafloor is Hempel's complete floor coating systems solution. Its highly technological and innovative formulas are designed to maximize your floor protection. The following are the standard recommended colours.




RAL 7035  
Hempel Code 11150




RAL 9010  
Hempel Code 10170



RAL 3001  
Hempel Code 57150




RAL 7040  
Hempel Code 17700



RAL 1013  
Hempel Code 17130



RAL 7042  
Hempel Code 17720



RAL 1015  
Hempel Code 27150



RAL 7046  
Hempel Code 17860



RAL 5005  
Hempel Code 37150



RAL 9005  
Hempel Code 19990



RAL 6024  
Hempel Code 47240

رغم استخدامنا أحدث تقنيات الطباعة والترسيب، إلا أن اللون في البطاقة قد يختلف عن لون المنتج الأصلي وذلك اعتماداً على المنتج ومقارنته ببقية المنتجات. كما أن تفاوت الألوان قد ينتج عن لمعة الطباعة أو عند إضافة السيليكا مثل السكريد. إذا تطلب معرفة اللون الحقيقي للمنتج ننصح بدهن عينة صغيرة قبل القيام بالاختيار النهائي للون المطلوب. كما يجب خلط المجموعات المختلفة قبل استخدامها لتفادي تباين الألوان.

إن دهانات الإيبوكسي سوف يصفر لونها وتتخلص وتفقد لمعانها مع مرور الوقت إذا تعرضت لضوء الشمس المباشر أو المنتشر.

واصفرار الدهان هو ظاهرة سطحية سببها أن المادة المكونة للدهان تعمق مع الزمن. هذا وتختلف درجة الاصفرار من منتج إلى آخر، ولكن ذلك لا يؤثر على فاعلية وأداء الدهان. وللحماية من أشعة الشمس فوق البنفسجية، نقترح إضافة توب كوت "همبافلور ديورابل 300" أو استشارة أحد خبراء همبل للمزيد من الخيارات.

الألوان الأخرى متاحة عند الطلب \* تخضع للحد الأدنى لكمية الطلب والمهلة الزمنية للتصنيع.

Although we have used the latest in printing and depositing technology, the actual colours may vary in reality depending on the product and when compared across the products. Deviation in colour can also be on account of different gloss and due to addition of Silica as in Scream. For critical colour matches, we recommend to apply on a small area for approval of the colour. Different batches should be blended before use to avoid colour variation.

Epoxy coatings will yellow, chalk and lose gloss over a period of time when exposed to direct or diffused sunlight. Yellowing is a surface phenomenon attributed to the natural darkening of epoxy resin. Degree of yellowing can vary from product to product. This has no influence on the function and performance of the coating. For UV protection, we suggest you to apply a top coat of Hempafloor Durable 300 or consult Hempel for more suitable options.

Other colours available upon request \* subject to minimum order quantity and lead time.